

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

LED street light

Name and address of the applicant

Ningbo Kangyan Lighting Electric Co. Ltd
Houyu Industry Area, Liangnong, 315430 Yuyao, Zhejiang, China

Name and address of the manufacturer

Ningbo Kangyan Lighting Electric Co. Ltd
Houyu Industry Area, Liangnong, 315430 Yuyao, Zhejiang, China

Name and address of the factory

Ningbo Kangyan Lighting Electric Co. Ltd
Houyu Industry Area, Liangnong, 315430 Yuyao, Zhejiang, China*When more than one factory*☐ Additional information on page 2

Ratings and principal characteristics

Product data

Ratings: 200 -240 V~ or 100-240 V~; 50/60 Hz; max 280 W; IP 66; Class II;
ta 50 °C
(for details please see annex model list in 6192416.50)

Trademark / Brand (if any)


KANGLIGHT or LUXIFIC

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Pisces-1 series, Pisces-2 series and Pisces-3 series

Additional information

☒ Additional information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2020, IEC 60598-2-3:2002 and
IEC 60598-2-3:2002/AMD1:2011National differences:
EU Group DifferencesAs shown in the Test Report Ref. No.
which forms part of this Certificate

6192416.50

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.
Meander 1051
6825 MJ Arnhem
Netherlands

Date: 2024-06-23

Signature: May Liu



Ref. Certif. No.

NL-108473

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

Additional information

Models see details refer to annex page 1 to 1

This CB Test Certificate is issued by the National Certification Body

DEKRA Certification B.V.
Meander 1051
6825 MJ Arnhem
Netherlands



Date: 2024-06-23

Signature: May Liu

Product name	Input voltage	LEDs (pcs)	Rated wattage (W)	Weight (Kg)	With/without NEMA or zhaga socket	
Pisces-1 series	200-240 V~; 50/60 Hz or 100-240 V~; 50/60 Hz	4~24	8~60	3-5	Without	
					With	
Pisces-2 series		8~54	20~150	4-6	Without	
					With	
Pisces-3 series		16~120	40~280	9-12	Without	
					With	

For models with other drivers, rated voltage range is 220-240V~.

[illegible]