

LUXERA

PRODUCT PROFILE

LUXERA-MIN and LUXERA-MID LED outdoor-lighting platforms with configuration-specific technical documentation.



LUXERA-MIN - identified test sample



LUXERA-MID - identified test sample

Two named platforms

Platform	Class I family envelope	ENEC+ reference
LUXERA-MIN	8-75 W; 8-36 LEDs	75 W; 3000 K; CRI 80
LUXERA-MID	8-150 W; 8-72 LEDs	110 W; 3000 K; CRI 70

Documents available

Technical datasheet; product catalogue; separate Class I and Class II certificate records. Certificate originals are available through the website resource centre.

Before quotation

Confirm the electrical class, complete model code, power, optics, mounting, driver and controls, quantities and destination. Configuration-specific measured sample data appears in the technical datasheet, clearly separated from rated values.

LUXIFIC Global project team
sales@kanglight.com
WhatsApp +86 139 5838 8144

Source references: ENEC 31-169826 and 31-175284; ENEC+ 31-169980 and 31-175826. Internal performance references 6251312.50P / 6251313.50P (sample-result tables and identified exterior photos); Class I safety reference 6251245.50, annex model list. References support traceability; full reports are not published.

This material is prepared from supplied certificates and internal test data. It is a configuration-specific technical summary, not a new certification. Original test reports and CAD files are not distributed. Confirm the final model code, driver, optics, mounting and current document scope before ordering.